

## TECHNICAL DATA SHEET F 50 MX

### PRODUCT LINE

41 F 50 MX	MAXXIMA YELLOW
42 F 50 MX	MAXXIMA MAGENTA
43 F 50 MX	MAXXIMA CYAN
49 F 50 MX	MAXXIMA BLACK

### APPLICATION

**INKREDIBLE MAXXIMA** has been designed for optimum performance, no compromises and optimum print results in any situation. **MAXXIMA** is a fast setting and quick drying sheetfed process series, which, due to its high resistance to mechanical stress, is suitable for a wide range of absorbent substrates. The strong, pure hues in combination with ideal trapping characteristics, ensure a captivating contrast in the printed image.

High press stability during production runs completes the profile for a maximum application process series. **MAXXIMA** meets the specification of DIN ISO 2846-1 and the color metric requirements of ISO 12 647-2.

### SPECIAL CHARACTERISTICS

Maximum suitability

- Optimum setting speed
- Optimum rub resistance
- Optimum gloss
- Optimum suitability for perfecting
- Maximum stability during production run
- Low start up waste
- Extremely fast adjustment to a stable ink-water balance
- Easy to handle with IPA-free printing using SUBSTIFIX®- AF

### RANGE OF APPLICATIONS

The process series **MAXXIMA** is ideally suited for different types of jobs on a wide range of substrates, where the highest demands are placed upon the inks. It is characterized by low dot gain, high dampening tolerance and high versatility.

### PROPERTIES

	Tack @ 1200rpm
41 F 50 MX	13.0-14.0
42 F 50 MX	14.0-15.0
43 F 50 MX	14.0-15.0
49 F 50 MX	13.5-14.5

### PACKAGING

Vacuum Sealed Cans	2.5 kg	5.5 lb
Cartridge	2 kg, 3.5 kg	4.4 lb, 7.7 lb