

CoatMax D 50.02 G SG

PX5002-39**Water based gloss coating**

KEY CHARACTERISTICS

- For board and paper
- No curling effect on thin paper
- High gloss finish
- Suited for offset off-line or in-line coaters
- Good rub/scuff resistance
- Good wet block resistance
- Solid content @ 45%
- Viscosity : 45s @30°C DIN #4 cup
- Density: approx 1.040 g/ml @25°C
- Colour: Milky white emulsion

FEATURES AND BENEFITS

- Good printability
- Highly flexible for use on thin paper
- Excellent gloss
- Excellent leveling & wetting
- Able to withstand high humidity/temperature storage conditions

PACKAGING

25 kg plastic can
120 kg plastic drum
1000 kg IBC

INSTRUCTIONS FOR USE

Use directly from container. It is highly recommended to shake/stir the contents before use for the optimum performance of the varnish. Do not leave product exposed to air. Some ingredients may evaporate and this will affect the physical properties and performance of the product. Check viscosity from time to time and add water when necessary to maintain the running viscosity.

TRANSPORT & STORAGE

Store at room temperature with container tightly closed when not in use in a cool, ventilated area. Protect from direct sunlight and keep away from heat sources. For details about health and safety, please consult the MSDS.

RECOMMENDED AUXILIARIES

Coating cleaner: special cleaner for the coating blankets and rollers
Anilox cleaning gel : to remove dried coating from the cells of the anilox roller