

XtraMax Water Flow S85

Concentrated water additive to be used in the automatic washing unit

KEY CHARACTERISTICS

- Specific density: 1,0115 g/ml
- Dosage: 5 %
- Water based
- For sheetfed, heatset and coldset application
- Protects against corrosion

PACKAGING

1000 L IBC
600 L IBC
200 L plastic drum
25 L jerrycan
4 x 5L jerrycan

FEATURES AND BENEFITS

Contains a corrosion inhibitor

- Prevents corrosion of all metal system parts

Low dosage

- Economical in use

Reduces surface tension

- Prevents dripping
- Improved wetting of the blanket
- Easy removal from paper dust

INSTRUCTIONS FOR USE

Add 5 % to the water circuit. Can be used for all cleaning systems with a separate water tank.

TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 °C or below -10 °C.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

Version 1.0, state 19/04/2013 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.