

Prinect Platform Requirements

1. Prinect Workflow Manager 10.01

1.1. Prinect Server

1.1.1. Minimum Hardware

- Dual CPU Intel Pentium IV Xeon processors with at least 2.4 GHz or two Intel Core 2 Duo processors with at least 2.4 GHz.
- 3.0 GByte RAM (4.0 GByte RAM for an all-in-one system, 8 GByte is recommended for Windows 2008 Server)
- Internal RAID 5; min.3x 74 GByte Disks
- DVD ROM drive
- Gigabit Ethernet network connection

1.1.2. Software

- MS Windows 2003 Server x86 SP2 or
MS Windows 2003 Server R2 x86 SP2 or
MS Windows Server 2008 Standard x64
MS Windows Server 2008 R2 x64
- Internet Access via MS Internet Explorer

1.2. Network Requirements

1.2.1. Network Performance/Bandwidth

- For sufficient system performance a switched Gigabit Ethernet network is required

1.2.2. Logical Grouping

- For proper system maintenance and access authentication it is required that the whole Prinect system (all Prinect workstations and servers) is either running completely in a Windows Workgroup OR in a Windows Domain.
- **It is mandatory that there is the same system time on all computers within the Prinect system environment. This has to be achieved by the usage of a central time server.**
- Name resolution must be properly configured
- No .local domain, if Mac Cockpits are present.